



# Non-Programmable Thermostats

Image	Description	Model	User Interface	Application				Power Method										Display Information			Limited Warranty	Wiring Terminals	Accessories Included
				Stages	Gas, Oil or Electric	Heat Pump	Millivolt	Linevolt	Permanent Memory Retention	Selectable Auto or Manual Changeover	Advanced Dual Fuel Heat Pump Operation	Comfort/Economy Mode	Temperature Setpoint Limits	Low Temperature Range	Remote Locator	Display Size (Viewable)	On-Demand Backlighting	Simultaneous Display of Room and Set Temperatures					
	Wireless FocusPRO® 5000 Non-Programmable	YTH5320R1116	Soft Keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•			Battery	•	•	•**	•	•	•***	5.09 sq. in.	•	•	5-Year	C, R, Rc, Rh, W-0/B, W2-AUX/E, Y, Y2, G, L, RAS, RAS	RedLINK Internet Gateway, Wireless Outdoor Sensor and Return Air Sensor		
		YTH5320R1000	Soft Keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•			Battery	•	•	•**	•	•	•***	5.09 sq. in.	•	•	5-Year	C, R, Rc, Rh, W-0/B, W2-AUX/E, Y, Y2, G, L, RAS, RAS	Wireless Outdoor Sensor and Return Air Sensor		
	PRO 3000 Non-Programmable	TH3110D1008	Slide switches	1 Heat/1 Cool	•		•		Dual powered (battery and hardwire)	•	Manual					1.32 sq. in.	•	•	5-Year	R, Rc, C, W, O, B, Y, G			
		TH3210D1004	Slide switches	2Heat/1 Cool Heat Pump					Dual powered (battery and hardwire)	•	Manual						1.32 sq. in.	•	•	5-Year	R, C, Y, Aux, O, B, E, G, L		
	PRO 1000 Non-Programmable	TH1110DV1009 Vertical	Slide switches	1 Heat/1 Cool	•	•	•		Dual powered (battery and hardwire)	•	Manual					1.0 sq. in.	•		2-Year	R, Rc, C, W, Y, G, O, B			
		TH1110DH1003 Horizontal	Slide switches	1 Heat/1 Cool	•	•	•		Dual powered (battery and hardwire)	•	Manual					1.0 sq. in.	•		2-Year	R, Rc, C, W, Y, G, O, B			
		TH1100DV1000 Vertical	Slide switches	1 Heat	•		•		Dual powered (battery and hardwire)	•	Manual			•		1.0 sq. in.	•		2-Year	R, C, W			
		TH1100DH1004 Horizontal	Slide switches	1 Heat	•		•		Dual powered (battery and hardwire)	•	Manual			•		1.0 sq. in.	•		2-Year	R, C, W			
		TH1210DV1007 Vertical	Slide switches	2 Heat/1 Cool Heat Pump			•		Dual powered (battery and hardwire)	•	Manual					1.0 sq. in.	•		2-Year	R, C, AUX/E, O, B, Y, G			
		TH1210DH1001 Horizontal	Slide switches	2 Heat/1 Cool Heat Pump			•		Dual powered (battery and hardwire)	•	Manual					1.0 sq. in.	•		2-Year	R, C, AUX/E, O, B, Y, G			
	The Digital Round™	T8775A1009	Dial	1 Heat	•				Power stealing	•						.75 sq. in.	•		5-Year	R, W			
		T8775C1005	Dial	1 Heat/1 Cool	•				Power stealing	•	Manual					.75 sq. in.	•		5-Year	R, Rc, W, O, B, Y, G			
	The Round™	T87K1007	Dial	1 Heat or 1 Cool	•				Battery assisted power stealing					50010944-001		N/A		•	5-Year	R, W			
		T87N1000	Dial	1 Heat/1 Cool	•				Battery assisted power stealing		Manual			50010944-001		N/A		•	5-Year	R, Rc, W, Y, G, O, B			
		T87N1026	Easy-To-See™	1 Heat/1 Cool	•				Battery assisted power stealing		Manual			50010944-001		N/A		•	5-Year	R, Rc, W, Y, G, O, B			
		T834N1002 Vertical	Slide switches and lever	1 Heat/1 Cool	•				Mechanical		Manual			50019661-001		N/A			5-Year	R, Rc, W, Y, G, O, B			
		T8034N1007 Horizontal	Slide switches and lever	1 Heat/1 Cool	•				Mechanical		Manual			50019661-001		N/A			5-Year	R, Rc, W, Y, G, O, B			
		T822K1000	Slide switches and lever	1 Heat	•				Mechanical		Positive off			50019661-001		N/A			5-Year	R, W			
		T822K1018	Slide switches and lever	1 Heat	•				Mechanical					50019661-001		N/A			5-Year	R, W			
		T827K1009	Slide switches and lever	1 Heat	•		•		Mechanical			Positive off			50019661-001		N/A			5-Year	R, W		
		TL7235A1003	Horizontal lays	1 Heat				•	208/240 V							2.67 sq. in.	•		5-Year	4 wire DPST			
		TL7230A1004	Dial	1 Heat				•	208/240 V							N/A			5-Year	DPST			
		T410/ T4398	Dial	1 Heat				•	120/208/240/277 V							N/A			1-Year	SPST or DPST			

\*REM5000R1001 required \*\*Controls dehumidification, humidification or ventilation \*\*\* Up to 4 Heat/2 Cool – Heat Pump. Up to 3 Heat/2 Cool – Conventional